NSN 3020-01-050-9373



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-050-9373 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 3.5417 inches **Teeth Quantity:** 170 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.164 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 3.541 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.875 inches first end **Face Width:** 0.300 inches **Bore Diameter:** 0.375 inches both ends **Hub Style Designator:** 1 step both ends **End Length:** 0.200 inches both ends **Precision Classification:** Quality number 12 **End Diameter:** 0.500 inches both ends First Step Length: 0.675 inches first end

First Step Diameter: 0.750 inches second end

NSN 3020-01-050-9373

Spur Gear - Page 2 of 2

Material:



Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t351 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1, class 1 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-a-8625 spec.