## NSN 3020-01-050-9375

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-050-9375

Body Style:
Webbed, solid
Pitch Diameter:
2.8125 inches
Teeth Quantity:
45
Bore Style:
10a w/ keyway both ends
Backlash Designation:
Grade c
Outside Diameter:
2.936 inches
Nominallength:
1.000 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.750 inches
Bore Diameter:
0.875 inches both ends
Keyway Width:
0.186 inches both ends
Distance From Bore Center To Keyway Bottom:
0.522 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
1.625 inches second end
Precision Classification:
Quality number 9
Material:
Steel comp 4620
Material Specification:
Mil-s-7493, comp 4620 military specification single material response
Style Designator:
One protruding hub, one flush hub
Shelf Life:
N/a

## NSN 3020-01-050-9375

Spur Gear - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7493 spec.