## NSN 3020-01-051-6498



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-051-6498 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7500 inches **Teeth Quantity:** 36 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.788 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.437 inches first end **Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Mil-std-171, finish no. 5.4.1 military standard single treatment response

**Style Designator:** 

Protruding hub

## NSN 3020-01-051-6498

Spur Gear - Page 2 of 2



Supplementary Features:
St2476,
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-std-171 spec.