## NSN 3020-01-052-2845

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-052-2845

| Attachment Method:  |
|---|
| Clamp   |
| Pitch Diameter:   |
| 1.2222 inches   |
| Teeth Quantity:   |
| 88  |
| Bore Style:   |
| Plain both ends   |
| Outside Diameter:   |
| 1.250 inches  |
| Tooth Form:   |
| Standard  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Distance Between Body Face And Protruding Hub End:                  |
| 0.221 inches first end  |
| Face Width:   |
| 0.104 inches  |
| Bore Diameter:  |
| 0.090 inches both ends  |
| Hub Style Designator:   |
| 1 step first end  |
| End Length:   |
| 0.189 inches first end  |
| Precision Classification:   |
| Quality number 10   |
| End Diameter:   |
| 0.187 inches first end  |
| First Step Length:  |
| 0.032 inches first end  |
| First Step Diameter:  |
| 0.250 inches first end  |
| Material:   |
| Steel comp 303 hub  |
| Material Specification:   |
| Qq-s-764 federal specification single material response hub         |
| Surface Treatment:  |
| Passivate hub   |
| Surface Treatment Specification:                                    |
| Qq-p-35, type 1 federal specification single treatment response hub |
| Style Designator:   |
| Produceding hosts   |

Protruding hub

## NSN 3020-01-052-2845

Spur Antibacklash Gear - Page 2 of 2



| N/a               |  |
|-------------------|--|
| Unit Of Measure:  |  |
|                   |  |
| Demilitarization: |  |
| No                |  |
| Fiig:             |  |
| A27300            |  |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: