NSN 3020-01-052-2845

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-052-2845

Attachment Method:
Clamp
Pitch Diameter:
1.2222 inches
Teeth Quantity:
88
Bore Style:
Plain both ends
Outside Diameter:
1.250 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.221 inches first end
Face Width:
0.104 inches
Bore Diameter:
0.090 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.189 inches first end
Precision Classification:
Quality number 10
End Diameter:
0.187 inches first end
First Step Length:
0.032 inches first end
First Step Diameter:
0.250 inches first end
Material:
Steel comp 303 hub
Material Specification:
Qq-s-764 federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response hub
Style Designator:
Produceding hosts

Protruding hub

NSN 3020-01-052-2845

Spur Antibacklash Gear - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A27300	

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: