## NSN 3020-01-052-2846

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-052-2846

Attachment Method:
Clamp  Pitch Diameter:
Between 1.4990 inches and 1.5000 inches
Teeth Quantity:
120
Bore Style: Plain both ends
Outside Diameter:
1.524 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:  0.221 inches first end
0.22
Face Width:
0.104 inches
Bore Diameter:
0.090 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.190 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.188 inches first end
First Step Length:
0.190 inches first end
First Step Diameter:
0.250 inches first end
Material:
Steel comp 303 hub
Material Specification:
Qq-s-764 federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response hub
Style Designator:
Protruding hub

## NSN 3020-01-052-2846

Spur Antibacklash Gear - Page 2 of 2



Chalf	1 :4~.
Shelf	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.