NSN 3020-01-052-4038

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-052-4038

Attachment Method:
Clamp
Pitch Diameter:
Between 0.5740 inches and 0.5750 inches
Teeth Quantity:
46
Bore Style:
Plain both ends
Outside Diameter:
0.6000 inches
Tooth Form:
Standard
Pressure Angle:
•
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.221 inches first end
Face Width:
0.104 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.188 inches first end
Clamping Surface Length:
0.190 inches first end
Precision Classification:
Quality number 10
Material:
Steel comp 303 hub
Material Specification:
Qq-s-764, cond a federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military specification single treatment response hub
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

--

NSN 3020-01-052-4038

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.