NSN 3020-01-054-6095



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-054-6095 **Body Style:** Webbed, solid Pitch Diameter: 5.0000 inches **Teeth Quantity:** 80 **Bore Style:** 10a w/ keyway both ends **Backlash Designation:** Grade c **Outside Diameter:** 5.124 inches Nominallength: 1.216 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.653 inches first end Face Width: 0.438 inches **Bore Diameter:** 0.875 inches both ends **Keyway Width:** 0.186 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.522 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 1.625 inches second end **Precision Classification:** Quality number 9

Hub Diameter:

1.625 inches second end

Precision Classification:

Quality number 9

Material:

Steel comp 4620

Material Specification:

Mil-s-7493, comp 4620 military specification single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

NSN 3020-01-054-6095

Spur Gear - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7493 spec.