NSN 3020-01-055-7643

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-055-7643 **Attachment Method:** Clamp **End Application:** Aircraft; f14a tomcat Pitch Diameter: 2.7500 inches **Teeth Quantity:** 176 **Bore Style:** Plain both ends **Outside Diameter:** 2.781 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.044 inches second end **Face Width:** 0.104 inches **Bore Diameter:** 0.312 inches second end **Hub Style Designator:** Plain second end **Hub Diameter:** 2.750 inches between body and flange **End Length:** 0.141 inches first end **End Diameter:** 0.312 inches first end First Step Length: 0.062 inches first end First Step Diameter: 0.302 inches first end **Second Step Length:** 0.078 inches first end **Second Step Diameter:** 0.500 inches first end Material:

Steel

Material Specification:

Qq-s-764 federal specification single material response

NSN 3020-01-055-7643

Mil-std-171 spec.

Spur Antibacklash Gear - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):