NSN 3020-01-058-5160

Spur Gear - Page 1 of 2

Body Style:

Webbed, offset, solid



View Online at https://aerobasegroup.com/nsn/3020-01-058-5160

| Attachment Method: | | |
|--|--|--|
| Mounting hole | | |
| Pitch Diameter: | | |
| 0.7292 inches | | |
| Teeth Quantity: | | |
| 70 | | |
| Bore Style: | | |
| Plain both ends | | |
| Backlash Designation: | | |
| Grade c | | |
| Mounting Hole Type And Quantity: | | |
| 2 countersunk axially through hub, first end | | |
| Outside Diameter: | | |
| 0.750 inches | | |
| Tooth Form: | | |
| Standard | | |
| Pressure Angle: | | |
| 20.0000 degrees | | |
| Distance Between Body Face And Protruding Hub End: | | |
| 0.150 inches first end | | |
| Body Recess Depth: | | |
| 0.125 inches second end | | |
| Face Width: | | |
| 0.100 inches | | |
| Bore Diameter: | | |
| 0.125 inches both ends | | |
| Hub Style Designator: | | |
| Plain first end | | |
| Hub Diameter: | | |
| 0.625 inches first end | | |
| Precision Classification: | | |
| Quality number 10 | | |
| Mounting Hole Diameter: | | |
| 0.116 inches axially through hub, first end | | |
| Bolt Hole Circle Diameter: | | |
| 0.350 inches axially through hub, first end | | |
| Material: | | |
| Aluminum alloy 2024 | | |
| Material Specification: | | |

Qq-a-225/6, t351 federal specification single material response

NSN 3020-01-058-5160

Spur Gear - Page 2 of 2



| Style | Design | ator: |
|-------|--------|-------|
| | | |

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300