## NSN 3020-01-058-5160

Spur Gear - Page 1 of 2

**Body Style:** 

Webbed, offset, solid



View Online at https://aerobasegroup.com/nsn/3020-01-058-5160

Attachment Method:		
Mounting hole		
Pitch Diameter:		
0.7292 inches		
Teeth Quantity:		
70		
Bore Style:		
Plain both ends		
Backlash Designation:		
Grade c		
Mounting Hole Type And Quantity:		
2 countersunk axially through hub, first end		
Outside Diameter:		
0.750 inches		
Tooth Form:		
Standard		
Pressure Angle:		
20.0000 degrees		
Distance Between Body Face And Protruding Hub End:		
0.150 inches first end		
Body Recess Depth:		
0.125 inches second end		
Face Width:		
0.100 inches		
Bore Diameter:		
0.125 inches both ends		
Hub Style Designator:		
Plain first end		
Hub Diameter:		
0.625 inches first end		
Precision Classification:		
Quality number 10		
Mounting Hole Diameter:		
0.116 inches axially through hub, first end		
Bolt Hole Circle Diameter:		
0.350 inches axially through hub, first end		
Material:		
Aluminum alloy 2024		
Material Specification:		

Qq-a-225/6, t351 federal specification single material response

## NSN 3020-01-058-5160

Spur Gear - Page 2 of 2



Style	Design	ator:

Protruding hub, recessed body

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300