NSN 3020-01-058-7933

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-058-7933

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.5208 inches
Teeth Quantity:
50
Backlash Designation:
Grade c
Mounting Hole Type And Quantity:
2 countersunk axially through body, first end
Outside Diameter:
0.541 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Body Recess Depth:
0.125 inches first end
Face Width:
0.250 inches
Precision Classification:
Quality number 10
Mounting Hole Diameter:
0.116 inches axially through body, first end
Bolt Hole Circle Diameter:
0.188 inches axially through body, first end
Material:
Steel comp 303
Material Specification:
Qq-s-764, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:
Hubless, recessed body
Shelf Life:
N/a
Unit Of Measure:

--

NSN 3020-01-058-7933

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.