NSN 3020-01-063-3908

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-063-3908

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| Between 0.3743 inches and 0.3750 inches |
| Teeth Quantity: |
| 27 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 0.402 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.188 inches first end |
| Face Width: |
| 0.093 inches |
| Bore Diameter: |
| 0.125 inches both ends |
| Hub Style Designator: |
| Pinned first end |
| Hub Diameter: |
| 0.312 inches first end |
| Precision Classification: |
| Quality number 12 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-764, type 303, cond a federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Mil-std-171, finish no. 5.4.1 military standard single treatment response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 3020-01-063-3908

Spur Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.