NSN 3020-01-064-6126

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-064-6126

view Offilitie at https://aerobasegroup.com/hsh/sozo-01-004-0120
Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.2500 inches
Teeth Quantity:
54
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 transversely through hub, first end
Mounting Hole Thread Size:
0.164 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
2.333 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.500 inches first end
Face Width:
0.250 inches
Bore Diameter:
0.313 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
0.750 inches second end
End Length:
0.265 inches first end
End Diameter:
0.500 inches first end
First Step Length:
0.234 inches first end
First Step Diameter:
0 COF inches first and

0.625 inches first end

NSN 3020-01-064-6126

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-b-18343 spec.



Special Features:
Mtg holes 90 degs apart centered on first end step
Material:
Copper alloy
Material Specification:
Mil-b-18343 military specification single material response
Style Designator:
One protruding hub, one flush hub
Furnished Items And Quantity:
2 setscrew
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300