NSN 3020-01-064-6126

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-064-6126

| view Offilitie at https://aerobasegroup.com/hsh/sozo-01-004-0120 |
|--|
| Body Style: |
| Webbed, offset, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 2.2500 inches |
| Teeth Quantity: |
| 54 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 32 transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.164 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 2 threaded transversely through hub, first end |
| Outside Diameter: |
| 2.333 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.500 inches first end |
| Face Width: |
| 0.250 inches |
| Bore Diameter: |
| 0.313 inches both ends |
| Hub Style Designator: |
| Plain second end |
| Hub Diameter: |
| 0.750 inches second end |
| End Length: |
| 0.265 inches first end |
| End Diameter: |
| 0.500 inches first end |
| First Step Length: |
| 0.234 inches first end |
| First Step Diameter: |
| 0 COF inches first and |

0.625 inches first end

NSN 3020-01-064-6126

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-b-18343 spec.



| Special Features: |
|---|
| Mtg holes 90 degs apart centered on first end step |
| Material: |
| Copper alloy |
| Material Specification: |
| Mil-b-18343 military specification single material response |
| Style Designator: |
| One protruding hub, one flush hub |
| Furnished Items And Quantity: |
| 2 setscrew |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |