## NSN 3020-01-067-3687

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-067-3687

Body Style:				
Plain, with lightening holes				
Attachment Method:				
Clamp				
Pitch Diameter:				
8.0000 inches				
Teeth Quantity:				
192				
Bore Style:				
Plain both ends				
Outside Diameter:				
8.081 inches				
Tooth Form:				
Stub				
Pressure Angle:				
20.0000 degrees				
Distance Between Body Face And Protruding Hub End:				
0.280 inches first end				
Face Width:				
0.380 inches				
Bore Diameter:				
0.313 inches both ends				
Hub Style Designator:				
Split first end				
Hub Diameter:				
Trub Diameter.				
0.375 inches first end				
0.375 inches first end				
0.375 inches first end Clamping Surface Length:				
0.375 inches first end  Clamping Surface Length:  0.250 inches first end				
0.375 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification:				
0.375 inches first end  Clamping Surface Length: 0.250 inches first end  Precision Classification:  Quality number 12				
0.375 inches first end  Clamping Surface Length: 0.250 inches first end  Precision Classification:  Quality number 12  Material:				
0.375 inches first end  Clamping Surface Length: 0.250 inches first end  Precision Classification:  Quality number 12  Material:  Aluminum alloy 2024				
0.375 inches first end  Clamping Surface Length: 0.250 inches first end  Precision Classification:  Quality number 12  Material:  Aluminum alloy 2024  Material Specification:				
0.375 inches first end  Clamping Surface Length: 0.250 inches first end  Precision Classification:  Quality number 12  Material:  Aluminum alloy 2024  Material Specification:  Qq-a-250/5, t4 federal specification single material response				
0.375 inches first end  Clamping Surface Length:  0.250 inches first end  Precision Classification:  Quality number 12  Material:  Aluminum alloy 2024  Material Specification:  Qq-a-250/5, t4 federal specification single material response  Surface Treatment:				
0.375 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 12 Material: Aluminum alloy 2024 Material Specification: Qq-a-250/5, t4 federal specification single material response Surface Treatment: Anodize				
0.375 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 12 Material: Aluminum alloy 2024 Material Specification: Qq-a-250/5, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification:				
0.375 inches first end Clamping Surface Length: 0.250 inches first end Precision Classification: Quality number 12 Material: Aluminum alloy 2024 Material Specification: Qq-a-250/5, t4 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 1, class 1 military specification single treatment response				

N/a

## NSN 3020-01-067-3687

Spur Gear - Page 2 of 2



ι	Jnit	Of	Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.