NSN 3020-01-070-0638

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-070-0638 **Attachment Method:** Clamp Pitch Diameter: 0.8750 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Outside Diameter:** 0.8910 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.297 inches first end **Face Width:** 0.100 inches **Bore Diameter:** 0.120 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.188 inches first end **Clamping Surface Length:** 0.172 inches first end **Precision Classification:** Quality number 10 Material: Steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-std-171, finish no. 5.4.1 military specification single treatment response Style Designator: Protruding hub Shelf Life: N/a

--

Unit Of Measure:

NSN 3020-01-070-0638

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.