## NSN 3020-01-071-4214

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-071-4214 **Attachment Method:** Clamp Pitch Diameter: 0.7500 inches **Teeth Quantity:** 54 **Bore Style:** Plain both ends **Outside Diameter:** 0.777 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.438 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.188 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.250 inches first end **Clamping Surface Length:** 0.250 inches first end **Precision Classification:** Quality number 10 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2, class 1 military specification single treatment response Style Designator: Protruding hub Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 3020-01-071-4214

Spur Antibacklash Gear - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.