NSN 3020-01-073-2321

Spur Gear - Page 1 of 2

Passivate



View Online at https://aerobasegroup.com/nsn/3020-01-073-2321 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.5000 inches **Teeth Quantity:** 40 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.525 inches Nominallength: 0.330 inches **Tooth Form:** Stub **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.180 inches first end **Face Width:** 0.150 inches **Bore Diameter:** 0.091 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.250 inches first end Material: Steel comp 303se **Material Specification:** Qq-s-764, type 303se, cond a federal specification single material response **Surface Treatment:**

NSN 3020-01-073-2321

Spur Gear - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-f-14072, finish e300 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.