NSN 3020-01-073-6006

Spur Gear - Page 1 of 2

Body Style: Plain, solid

Attachment Method:



View Online at https://aerobasegroup.com/nsn/3020-01-073-6006

Mounting hole
Pitch Diameter:
1.2500 inches
Teeth Quantity:
20
Bore Style:
W/ keyway both ends
Features Provided:
Casehardened
Mounting Hole Thread Series Designator:
Unf axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through body, first end
Hardness Rating:
34.0 rockwell c and 38.0 rockwell c
Mounting Hole Thread Size:
0.190 inches axially through body, first end
Mounting Hole Type And Quantity:
2 threaded axially through body, first end
Outside Diameter:
1.350 inches
Tooth Form:
Stub
Pressure Angle:
20.0000 degrees
Face Width:
0.625 inches
Bore Diameter:
0.749 inches both ends
Keyway Width:
0.188 inches both ends
Distance From Bore Center To Keyway Bottom:
0.460 inches both ends
Material:
Steel
Material Specification:
Mil-s-6709 military specification single material response
Surface Treatment:
Phosphate manganese

NSN 3020-01-073-6006

Spur Gear - Page 2 of 2



Surface Treatment Speci

171, finish no. 5.3.1.2 military standard single treatment response

Style Designator:

Hubless

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-6709 spec.