## NSN 3020-01-073-6006

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-073-6006

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 1.2500 inches **Teeth Quantity:** 20 **Bore Style:** W/ keyway both ends **Features Provided:** Casehardened Mounting Hole Thread Series Designator: Unf axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 32 axially through body, first end Hardness Rating: 34.0 rockwell c and 38.0 rockwell c Mounting Hole Thread Size: 0.190 inches axially through body, first end Mounting Hole Type And Quantity: 2 threaded axially through body, first end **Outside Diameter:** 1.350 inches **Tooth Form:** Stub **Pressure Angle:** 20.0000 degrees Face Width: 0.625 inches **Bore Diameter:** 0.749 inches both ends **Keyway Width:** 0.188 inches both ends Distance From Bore Center To Keyway Bottom: 0.460 inches both ends Material: Steel **Material Specification:** Mil-s-6709 military specification single material response **Surface Treatment:** 

Phosphate manganese

# NSN 3020-01-073-6006

Spur Gear - Page 2 of 2



#### Surface Treatment Specification:

171, finish no. 5.3.1.2 military standard single treatment response

#### Style Designator:

Hubless

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-6709 spec.