## NSN 3020-01-075-0666

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-075-0666

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.7000 inches
Teeth Quantity:
56
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 axially through hub, first end
Mounting Hole Thread Size:
0.086 inches axially through hub, first end
Mounting Hole Type And Quantity:
2 threaded axially through hub, first end
Outside Diameter:
0.725 inches
Tooth Form:
Stub
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.062 inches first end
Face Width:
0.156 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.310 inches first end
End Length:
0.014 inches second end
End Diameter:
0.190 inches second end
First Step Length:
0.018 inches second end
First Step Diameter:
0.250 inches second end

## NSN 3020-01-075-0666

Spur Gear - Page 2 of 2

Material:

Mil-s-5002 spec.



Steel comp 303
Material Specification:
Qq-s-763, class 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):