NSN 3020-01-075-9203

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-075-9203

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.4295 inches and 0.4455 inches
Teeth Quantity:
35
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
80 axially through hub, first end
Mounting Hole Thread Size:
0.060 inches axially through hub, first end
Mounting Hole Type And Quantity:
1 threaded axially through hub, first end
Outside Diameter:
0.462 inches
Nominallength:
0.265 inches
Tooth Form:
Stub
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.010 inches second end
Face Width:
0.045 inches
Bore Diameter:
0.094 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
0.130 inches second end
End Length:
0.008 inches first end
End Diameter:
0.130 inches first end
First Step Length:

0.008 inches first end

NSN 3020-01-075-9203 Spur Gear - Page 2 of 2

Fiig: A27300



First Step Diameter:
0.250 inches first end
Material:
Aluminum alloy 7075
Material Specification:
Qq-a-225/9, t6 federal specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No