

View Online at <https://aerobasegroup.com/nsn/3020-01-077-4411>

Groove Depth:

0.560 inches

Groove Width:

0.515 inches

Outside Diameter:

10.200 inches

Overall Length:

2.180 inches

Bolt Circle Diameter:

2.750 inches

Bore Length:

1.060 inches

Drilled Hole Diameter:

0.656 inches

V Groove Angle In Deg:

18.0

Securing Hole Quantity:

6

Taper Bore Major Diameter:

0.750 inches

Material And Location:

Any acceptable

Face Width:

1.365 inches

Design Form:

Webbed

Bore Type:

Tapered

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Through pulley body

Keying Facility:

Not included

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Pulley surface

Hub End Outside Diameter And Location:

6.750 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.815 inches aa end and 1.120 inches bb end

First Step Face Largest Diameter And Location:

6.750 inches aa end

First Step Length And Location:

0.245 inches aa end

Second Step Length And Location:

0.130 inches aa end

Hub End Outside Diameter And Location:

1.380 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.815 inches aa end

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a