# NSN 3020-01-078-1071

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-078-1071

#### **Pitch Diameter:**

0.8375 inches

## **Teeth Quantity:**

67

## Bore Style:

Plain both ends

## Outside Diameter:

0.8625 inches

#### **Tooth Form:**

Standard

#### **Pressure Angle:**

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

#### 0.221 inches first end

Face Width:

### 0.104 inches

# Bore Diameter:

0.125 inches both ends

# Hub Style Designator:

Pinned first end

## Hub Diameter:

0.312 inches first end

### **Precision Classification:**

Quality number 12

### Material:

Steel spring

## **Material Specification:**

Qq-s-763 federal specification single material response hub

#### Surface Treatment:

Passivate hub

## Surface Treatment Specification:

Ms171, finish no. 5.4.1 military standard single treatment response hub

#### Style Designator:

Protruding hub

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A27300

NSN 3020-01-078-1071

Spur Antibacklash Gear - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

