NSN 3020-01-078-7672

Spur Gear - Page 1 of 2

Body Style: Plain, solid



View Online at https://aerobasegroup.com/nsn/3020-01-078-7672

Attachment Method:		
Mounting hole		
Pitch Diameter:		
0.7500 inches		
Teeth Quantity:		
18		
Bore Style:		
Plain both ends		
Backlash Designation:		
Grade c		
Mounting Hole Type And Quantity:		
2 plain axially through flange		
Outside Diameter:		
0.0833 inches		
Tooth Form:		
Standard		
Pressure Angle:		
20.0000 degrees		
Distance Between Body Face And Protruding Hub End:		
0.250 inches first end		
Face Width:		
0.250 inches		
Bore Diameter:		
0.2503 inches both ends		
Hub Style Designator:		
Plain first end		
Hub Diameter:		
0.500 inches first end		
Precision Classification:		
Quality number 10		
Mounting Hole Diameter:		
0.099 inches axially through flange		
Special Features:		
Designed to mate w/p/n 12271639		
Material:		
Aluminum alloy 2024		
Material Specification:		
Qq-a-225/6 2024-t4 federal specification single material response		
Surface Treatment:		
Oxide film		

NSN 3020-01-078-7672

Spur Gear - Page 2 of 2



Surface	Treatment	Specification:
---------	------------------	----------------

Mil-c-5541 cl 1a military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.