NSN 3020-01-079-9723

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-079-9723

Body Style:
Plain, solid
Pitch Diameter:
1.3091 inches
Teeth Quantity:
47
Bore Style:
10a w/ keyway both ends
Backlash Designation:
Grade a
Hardness Rating:
40.0 rockwell c and 48.0 rockwell c
Outside Diameter:
1.364 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.161 inches first end
Face Width:
1.3091 inches
Bore Diameter:
0.378 inches both ends
Keyway Width:
0.094 inches both ends
Distance From Bore Center To Keyway Bottom:
0.2345 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.378 inches first end
Material:
Steel comp 630
Material Specification:
Ams 5643 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, finish no. 5.4.1 military standard single treatment response
Style Designator:

Protruding hub

NSN 3020-01-079-9723

Spur Gear - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.