NSN 3020-01-083-0984

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-083-0984

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 0.5417 inches |
| Teeth Quantity: |
| 52 |
| Bore Style: |
| W/counterbore counter bore, second end |
| Mounting Hole Thread Series Designator: |
| Unc axially through flange |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 56 axially through flange |
| Mounting Hole Thread Size: |
| 0.086 inches axially through flange |
| Mounting Hole Type And Quantity: |
| 3 threaded axially through flange |
| Outside Diameter: |
| 0.563 inches |
| Tooth Form: |
| Standard |
| Flange Diameter: |
| 1.062 inches |
| Pilot Length: |
| 0.052 inches |
| Pressure Angle: |
| 20.0000 degrees |
| Flange Thickness: |
| 0.042 inches |
| Face Width: |
| 0.219 inches |
| Bore Diameter: |
| 0.3125 inches counter bore, second end |
| Distance Between Outer Body Face And Inner Flange Face: |
| 0.2656 inches |
| Counterbore Depth: |
| 0.0312 inches counter bore, second end |
| Counterbore Diameter: |
| 0.375 inches counter bore, second end |
| Hub Diameter: |
| 0.500 inches between body and flange |
| |

NSN 3020-01-083-0984

Spur Gear - Page 2 of 2



Pilot Diameter:

0.7812 inches

Bolt Hole Circle Diameter:

0.656 inches axially through flange

Material:

Stainless steel

Surface Treatment:

Passivate

Style Designator:

Flanged end with pilot

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300