NSN 3020-01-084-1578



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-084-1578 **Attachment Method:** Clamp and mounting hole **End Application:** Wsr-74c radar, lwr Pitch Diameter: Between 1.3115 inches and 1.3125 inches **Teeth Quantity:** 84 **Backlash Designation:** Grade e **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end Nominallength: 0.385 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end **Face Width:** 0.104 inches **Hub Diameter:** 0.248 inches first end **Clamping Surface Length:** 0.250 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Qq-p-35, type 1 federal specification single treatment response **Style Designator:** Protruding hub

N/a
Unit Of Measure:

Shelf Life:

NSN 3020-01-084-1578

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300