

View Online at <https://aerobasegroup.com/nsn/3020-01-084-9765>

Counterbore Diameter:

2.380 inches

Counterbore Depth:

0.470 inches

Groove Depth:

0.620 inches

Groove Width:

0.597 inches

Outside Diameter:

7.494 inches

Overall Length:

4.391 inches

Keyway Width:

0.314 inches

Thread Size:

3/8-16

Bore Diameter:

1.812 inches

Bore Length:

4.340 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.060 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

7.374 inches

Securing Hole Quantity:

6

Material And Location:

Iron, cast

Face Width:

1.710 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Included

Counterbore Location:

Bb end

Hole Location:

Equally spaced around bore on 4.690 in bolt circle dia, 0.750 in. Dp

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Bb end

Hub End Outside Diameter And Location:

2.624 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

1.771 inches aa end and 0.921 inches bb end

First Step Face Largest Diameter And Location:

2.345 inches aa end

Second Step Face Largest Diameter And Location:

9.340 inches aa end

First Step Length And Location:

0.391 inches aa end

Second Step Length And Location:

0.910 inches aa end

Hub End Outside Diameter And Location:

2.624 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

2.881 inches aa end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a