NSN 3020-01-084-9765



Groove Pulley - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/3020-01-084-9765 **Counterbore Diameter:** 2.380 inches **Counterbore Depth:** 0.470 inches **Groove Depth:** 0.620 inches **Groove Width:** 0.597 inches **Outside Diameter:** 7.494 inches **Overall Length:** 4.391 inches **Keyway Width:** 0.314 inches **Thread Size:** 3/8-16 **Bore Diameter:** 1.812 inches **Bore Length:** 4.340 inches **Distance From Center Of Bore To Bottom Of Keyway:** 1.060 inches V Groove Angle In Deg: 36.0 Pitch Diameter: 7.374 inches **Securing Hole Quantity: Material And Location:** Iron, cast **Face Width:** 1.710 inches **Design Form:** Spoked **Bore Type:** Straight Bearings: Not included **Groove Quantity:**

2

Counterbore Feature:

Included

NSN 3020-01-084-9765 Groove Pulley - Page 2 of 3



Counterbore Location:
Bb end
Hole Location:
Equally spaced around bore on 4.690 in bolt circle dia, 0.750 in. Dp
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Threaded hole
Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Not offset
Lightening Hole:
Not included
Integral Cooling Vane:
Included
Groove Shape:
V
Bore Feature:
Included
Protruding Hub Characteristic:
Stepped
2.51.1.5
Securing Location:
Securing Location:
Securing Location: Bb end
Securing Location: Bb end Hub End Outside Diameter And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location: 0.391 inches aa end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location: 0.391 inches aa end Second Step Length And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location: 0.391 inches aa end Second Step Length And Location: 0.910 inches aa end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location: 0.391 inches aa end Second Step Length And Location: 0.910 inches aa end Hub End Outside Diameter And Location:
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location: 0.391 inches aa end Second Step Length And Location: 0.910 inches aa end Hub End Outside Diameter And Location: 2.624 inches aa end
Securing Location: Bb end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.771 inches aa end and 0.921 inches bb end First Step Face Largest Diameter And Location: 2.345 inches aa end Second Step Face Largest Diameter And Location: 9.340 inches aa end First Step Length And Location: 0.391 inches aa end Second Step Length And Location: 0.910 inches aa end Hub End Outside Diameter And Location: 2.624 inches aa end Distance From Outside Flange/rim To Hub End And Location:

NSN 3020-01-084-9765

Groove Pulley - Page 3 of 3



Sty	υt	-51	u	เลเ	u	I -

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a