## NSN 3020-01-086-5919

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-086-5919

Attachment Method:
Clamp
Pitch Diameter:
Between 1.9521 inches and 1.9531 inches
Teeth Quantity:
125
Bore Style:
Plain both ends
Outside Diameter:
1.9840 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.104 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.250 inches first end
Precision Classification:
Quality number 10
End Diameter:
0.312 inches first end
First Step Length:
0.031 inches first end
First Step Diameter:
0.375 inches first end
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response
Style Designator:
Protruding hub

## NSN 3020-01-086-5919

Spur Antibacklash Gear - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300