## NSN 3020-01-088-1012

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-088-1012 **Body Style:** Plain, solid **Attachment Method:** Clamp Pitch Diameter: 0.8750 inches **Teeth Quantity:** 84 **Bore Style:** Plain both ends **Outside Diameter:** 0.896 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.281 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches first end **Hub Style Designator:** Split first end **Hub Diameter:** 0.188 inches first end **Clamping Surface Length:** 0.250 inches first end **Precision Classification:** Quality number 10 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response **Surface Treatment:** Anodize hub **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response hub **Style Designator:** Protruding hub Shelf Life:

N/a

## NSN 3020-01-088-1012

Spur Gear - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.