NSN 3020-01-093-9395

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-093-9395

| Overall Length: |
|---|
| 0.312 inches |
| Keyway Width: |
| 0.096 inches |
| Bore Diameter: |
| 0.375 inches |
| Bore Length: |
| 0.158 inches |
| Distance From Center Of Bore To Bottom Of Keyway: |
| 0.236 inches |
| Face Width: |
| 0.110 inches |
| Guide: |
| Not included |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Keying Facility: |
| Included |
| Keying Facility Type: |
| Keyway |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Belt/chain/film Size For Which Designed: |
| Silent chain |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 18 |
| Asa Standard Chain Number: |
| 25 |
| Bore Bearing: |
| Not included |
| Hub External Keyway: |
| Not included |
| Hub End Outside Diameter And Location: |
| 1.000 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |

0.202 inches aa end and 0.153 inches bb end

NSN 3020-01-093-9395 Sprocket Wheel - Page 2 of 2



| Special Features: |
|-----------------------------------|
| Used on Igm-30 elevator work cage |
| Material: |
| Steel |
| Material: |
| Steel |
| Quantity: |
| 1 |
| Style Designator: |
| Webbed or spoked |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: Т353-с