NSN 3020-01-094-3117

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-094-3117

Attachment Method:
Mounting hole
Pitch Diameter:
Between 1.2493 inches and 1.2500 inches
Teeth Quantity:
40
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.138 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.3120 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.406 inches first end
Face Width:
0.188 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.375 inches first end
Precision Classification:
Quality number 12
End Diameter:
0.438 inches first end
First Step Length:
0.031 inches first end
First Step Diameter:
0.500 inches first end
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response

NSN 3020-01-094-3117

Spur Antibacklash Gear - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-std-171, finish no. 5.4.1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-std-171 spec.