NSN 3020-01-094-4591

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-094-4591 **Attachment Method:** Clamp Pitch Diameter: 0.9375 inches **Teeth Quantity:** 45 **Bore Style:** Plain both ends **Outside Diameter:** 0.978 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.313 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.240 inches both ends **Hub Style Designator:** 2 steps first end **End Length:** 0.250 inches first end **Precision Classification:** Quality number 12 **End Diameter:** 0.312 inches first end First Step Length: 0.032 inches first end First Step Diameter: 0.375 inches first end Second Step Length: 0.031 inches first end **Second Step Diameter:** 0.500 inches first end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-25074 federal specification single material response

Surface Treatment: Anodize

NSN 3020-01-094-4591

Spur Antibacklash Gear - Page 2 of 2



Mil-a-8625, type 1, class 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.