NSN 3020-01-095-6877



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-095-6877 **Outside Diameter:** 17.785 inches **Overall Length:** 7.875 inches **Outside Diameter:** 18.000 inches **Thread Size:** 1/2-13 **End Application:** Used on hydraulic start pump on s.S. Generator onboard 378 ft whec coast guard vessels Pitch Diameter: 17.905 inches **Securing Hole Quantity: Face Width:** 7.500 inches **Guide:** Included **Design Form:** Spoked **Hole Location:** On hub side **Guide Type:** Sprocket side flange **Securing Method:** Key or threaded hole **Lightening Hole:** Not included **Securing Location:** Aa end Belt/chain/film Size For Which Designed: Positive drive belt **Teeth Row Quantity:** 1 **Teeth Quantity Per Row: Hardness Rating Test Method:** Not rated **Bore Bearing:** Not included

Tooth Pitch: 1.250 inches

NSN 3020-01-095-6877

Sprocket Wheel - Page 2 of 2

No Fiig: T353-c



Hub End Outside Diameter And Location: 5.500 inches aa end **Distance From Outside Flange/rim To Hub End And Location:** 0.188 inches aa end Material: Aluminum alloy, qq-a-355-canceled Material: Aluminum alloy 2024 **Material Specification:** Qq-a-355-canceled federal specification single material response Style Designator: Webbed or spoked Shelf Life: N/a **Unit Of Measure:** Demilitarization: