NSN 3020-01-096-6484

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-096-6484 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.4786 inches and 0.4791 inches **Teeth Quantity:** 23 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end Nominallength: 0.500 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.250 inches **Bore Diameter:** 0.250 inches both ends **Hub Diameter:** 0.500 inches first end **Precision Classification:** Quality number 14 Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Style Designator:** Protruding hub Shelf Life:

N/a

NSN 3020-01-096-6484

Spur Gear - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.