# NSN 3020-01-099-6178

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-099-6178

# **Body Style:**

Webbed, offset, solid

# **Attachment Method:**

Mounting hole

# Pitch Diameter:

Between 0.8075 inches and 0.8175 inches

# **Teeth Quantity:**

39

Bore Style:

Plain both ends

# **Backlash Designation:**

Grade c

#### Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

# Mounting Hole Thready Qty Per Inch (tpi):

40 transversely through hub, first end

#### Mounting Hole Thread Size:

0.112 inches transversely through hub, first end

# Mounting Hole Type And Quantity:

1 plain transversely through hub, first end and 1 threaded transversely through hub, first end

# Outside Diameter:

0.853 inches

# Nominallength:

0.312 inches

# Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.222 inches first end

# Body Recess Depth:

0.050 inches second end

#### Face Width:

0.090 inches

#### **Bore Diameter:**

0.265 inches both ends

#### Hub Diameter:

0.500 inches first end

# **Precision Classification:**

Quality number 8

#### Mounting Hole Diameter:

0.043 inches transversely through hub, first end

# NSN 3020-01-099-6178

Spur Gear - Page 2 of 2



# Material:

Aluminum alloy 2024

## **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

#### Surface Treatment:

Chromate

# Surface Treatment Specification:

Mil-c-5541, type 1 military specification single treatment response

# Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A27300

# Mil-std (military Standard):

Mil-c-5541 spec.