

View Online at <https://aerobasegroup.com/nsn/3020-01-102-1462>

Outside Diameter:

Between 1.374 inches and 1.376 inches

Overall Length:

1.500 inches

Keyway Width:

Between 0.188 inches and 0.190 inches

Bore Diameter:

Between 0.6255 inches and 0.6265 inches

Bore Length:

1.500 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.4015 inches and 0.4025 inches

Material And Location:

Aluminum alloy, qq-a-225/8, alloy 6061, t6

Face Width:

1.000 inches

Design Form:

Plain

Bore Type:

Straight

Bearings:

Not included

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Clamp

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Crown Face:

Included

Rim Type:

Solid

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Hub End Outside Diameter And Location:

1.390 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.500 inches aa end

Special Features:

Securing clamp integral with pulley body

Quantity:

1

Surface Treatment:

Anodize

Style Designator:

Plain

Surface Treatment:

Anodized

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a