NSN 3020-01-102-1462

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-102-1462 **Outside Diameter:** Between 1.374 inches and 1.376 inches **Overall Length:** 1.500 inches **Keyway Width:** Between 0.188 inches and 0.190 inches **Bore Diameter:** Between 0.6255 inches and 0.6265 inches Bore Length: 1.500 inches Distance From Center Of Bore To Bottom Of Keyway: Between 0.4015 inches and 0.4025 inches **Material And Location:** Aluminum alloy, qq-a-225/8, alloy 6061, t6 **Face Width:** 1.000 inches **Design Form:** Plain **Bore Type:** Straight Bearings: Not included **Counterbore Feature:** Not included **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Clamp **Split Hub Feature:** Not included **Lightening Hole:** Not included **Integral Cooling Vane:** Not included **Crown Face:** Included Rim Type: Solid **Bore Feature:**

Included

NSN 3020-01-102-1462 Flat Pulley - Page 2 of 2



Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Hub End Outside Diameter And Location:
1.390 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.500 inches aa end
Special Features:
Securing clamp integral with pulley body
Quantity:
1
Surface Treatment:
Anodize
Style Designator:
Plain
Surface Treatment:
Anodized
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
T353-a