NSN 3020-01-103-2492

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-103-2492

Attachment Method:
Mounting hole
Pitch Diameter:
1.1500 inches
Teeth Quantity:
92
Bore Style:
Plain both ends
Backlash Designation:
Grade e
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.1725 inches
Nominallength:
0.325 inches
Tooth Form:
Special
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.221 inches first end
Face Width:
0.1041 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.313 inches first end
Material:
Steel comp 303
Material Specification:
Aisi 303 federal standard single material response
Surface Treatment:
Passivate

NSN 3020-01-103-2492

Spur Antibacklash Gear - Page 2 of 2

Style Designator:

Protruding hub

Furnished Items And Quantity:

1 setscrew

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

