NSN 3020-01-105-0109

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-105-0109

View Online at https://aerobasegroup.com/nsn/3020
Outside Diameter:
Between 1.7200 inches and 1.7300 inches
Overall Length:
Between 0.6150 inches and 0.6250 inches
Bore Diameter:
Between 0.625 inches and 0.627 inches
Bore Length:
Between 0.9450 inches and 0.9550 inches
Drilled Hole Diameter:
0.115 inches
Pitch Diameter:
Between 1.4600 inches and 1.4640 inches
Securing Hole Quantity:
1
Face Width:
Between 0.1030 inches and 0.1100 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
On sprocket face
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:

20

NSN 3020-01-105-0109 Sprocket Wheel - Page 2 of 2



Asa Standard Chain Number:
25
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.250 inches
Hub End Outside Diameter And Location:
1.125 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.515 inches aa end
Material:
Aluminum alloy, qq-a-200/11, t6
Material:
Aluminum alloy 7075
Material Specification:
Qq-a-200/11, t6 federal specification single material response
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
Yes - demil/mli
Fiig:
T353-c