## NSN 3020-01-108-0281

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-108-0281

Body Style:

Plain, solid

**Attachment Method:** 

Clamp

**Pitch Diameter:** 

0.9688 inches

**Teeth Quantity:** 

93

Bore Style:

Plain both ends

Outside Diameter:

0.989 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.155 inches first end

Face Width:

0.095 inches

Bore Diameter:

0.155 inches both ends

Hub Style Designator:

Split first end

Hub Diameter:

0.155 inches first end

**Clamping Surface Length:** 

0.155 inches first end

**Precision Classification:** 

Quality number 10 or quality number 11

Material:

Steel comp 302 and steel comp 303

### Material Specification:

Mil-s-7720, cond a military specification 1st material response or qq-s-764, cond a federal specification 2nd material response

### Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

# NSN 3020-01-108-0281

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.

