

View Online at <https://aerobasegroup.com/nsn/3020-01-108-4178>

**Outside Diameter:**

4.982 inches

**Overall Length:**

2.000 inches

**Keyway Width:**

0.376 inches

**Bore Diameter:**

Between 1.625 inches and 1.627 inches

**Bore Length:**

2.000 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

1.014 inches

**Pitch Diameter:**

4.610 inches

**Face Width:**

0.569 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Metallic Hardness Rating And Location:**

40.0 rockwell c body and 55.0 rockwell c body

**Counterbore Feature:**

Not included

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Stepped

**Groove/step Location:**

Both ends

**Belt/chain/film Size For Which Designed:**

Roller chain

**Roller Chain Pitch Type For Which Designed:**

Double pitch

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

14

**Hardness Rating Test Method:**

Rockwell

**Teeth Hardness Rating:**

Between 40.0 rockwell c and 55.0 rockwell c

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

2.000 inches

**First Step Face Largest Diameter And Location:**

3.100 inches both ends

**First Step Length And Location:**

0.062 inches both ends

**Second Step Length And Location:**

0.656 inches aa end and 0.651 inches bb end

**Hub End Outside Diameter And Location:**

1.810 inches both ends

**Material:**

Steel, mil-s-7720

**Material:**

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 316

**Material Specification:**

Mil-s-7720 military specification single material response

**Quantity:**

1

**Style Designator:**

Plain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c

**Mil-std (military Standard):**

Mil-s-7720 spec.