NSN 3020-01-111-4890

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-111-4890
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
8.3125 inches
Teeth Quantity:
399
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thread Size:
0.132 inches axially through body, first end
Mounting Hole Type And Quantity:
8 counterbored axially through body, first end and 4 threaded axially through body, first end
Outside Diameter:
8.354 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.260 inches first end
Face Width:
0.210 inches
Bore Diameter:
5.500 inches both ends
Counterbore Depth:
0.235 inches counter bore, second end
Counterbore Diameter:
8.002 inches counterbore, first end
Hub Style Designator:
Plain first end
Hub Diameter:
8.200 inches first end
Precision Classification:
Quality number 8
Mounting Hole Diameter:
0.166 inches axially through body, first end
Bolt Hole Circle Diameter:
6.800 inches axially through body, first end and 6.800 inches axially through body, first end

NSN 3020-01-111-4890

Spur Gear - Page 2 of 2



Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, t351 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.