NSN 3020-01-113-0039

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-113-0039

| Outside Diameter: |
|--|
| 0.962 inches |
| Overall Length: |
| 0.375 inches |
| Thread Size: |
| 6-32 |
| Bore Diameter: |
| 0.250 inches |
| Bore Length: |
| 0.375 inches |
| Pitch Diameter: |
| 0.900 inches |
| Securing Hole Quantity: |
| 1 |
| Furnished Items And Quantity: |
| Setscrew, one each |
| Face Width: |
| 0.125 inches |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Hole Location: |
| 0.120 in.From end of hub |
| Keying Facility: |
| Not included |
| Securing Method: |
| Threaded hole |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Belt/chain/film Size For Which Designed: |
| Cable chain |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 18 |
| Hardness Rating Test Method: |

Not rated

NSN 3020-01-113-0039 Sprocket Wheel - Page 2 of 2



| Bore Bearing: |
|---|
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 0.157 inches |
| Hub End Outside Diameter And Location: |
| 0.500 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.250 inches aa end |
| Material: |
| Aluminum alloy |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Anodized |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-c |