NSN 3020-01-113-5418

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-113-5418 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.9167 inches **Teeth Quantity:** 22 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches axially through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.956 inches Nominallength: 0.370 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.188 inches first end **Face Width:** 0.188 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.437 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Steel comp 416 **Material Specification:** Qq-s-763, class416 federal specification single material response

NSN 3020-01-113-5418

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-std-171 spec.



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-std-171, 5.4 military standard single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A27300