NSN 3020-01-115-2814

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-115-2814

Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.6553 inches and 2.6563 inches
Teeth Quantity:
170
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
2.688 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.104 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.250 inches first end
Precision Classification:
Quality number 10
End Diameter:
0.310 inches first end
First Step Length:
0.031 inches first end
First Step Diameter:
0.312 inches first end
Material:
Steel comp 303
Material Specification:
Qq-s-764 federal specification single material response

NSN 3020-01-115-2814

Spur Antibacklash Gear - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A27300