NSN 3020-01-115-2816

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-115-2816 **Attachment Method:** Mounting hole Pitch Diameter: 3.6250 inches **Teeth Quantity:** 232 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 3.6560 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end Face Width: 0.104 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.250 inches first end **Precision Classification:** Quality number 10 **End Diameter:** 0.500 inches first end First Step Length: 0.031 inches first end First Step Diameter: 0.438 inches first end Material: Steel comp 303

Material Specification:

Qq-s-764, type 303 federal specification single material response

NSN 3020-01-115-2816 Spur Antibacklash Gear - Page 2 of 2



Surface Treatment:
Passivate hub
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A27300